















Effective from December 2025, subject to change without notice. SRP in SEK incl. VAT

Power Conditioners		SRP
POWERMASTER		
Flagship Model. 12 outputs. DC Blocker, Distribution bars - silvered OFC 90 QMM, Multipoint PCB terminals, Ground noise filtering system		
	with LS-2 EVO cable	275 000
PC-4 EVO+ ver.'24		
Reference Model. 12 outputs. DC Blocker. Distribution bars - silvered OFC 45 QMM. Internal wiring - silvered OFHC 4 QMM.		
	with LS-2 EVO cable	154 500
	with LS-1 EVO+ cable	141 100
	with PowerSync ULTRA cable	131 100
PC-3 SE EVO+		
6 outputs. DC Blocker. Distribution bars - silvered OFC 30 QMM. Internal wiring - silvered OFHC 4 QMM.		
	with LS-2 EVO cable	113 800
	with LS-1 EVO+ cable	99 800
	with PowerSync ULTRA cable	89 200
	with LC-2 EVO cable	83 600
PC-3 EVO+		
6 outputs. DC Blocker. Distribution bars - OFC 30 QMM. Internal wiring - silvered OFHC 4 QMM.		
	with LS-1 EVO+ cable	83 100
	with PowerSync ULTRA cable	73 100
	with LC-2 EVO cable	67 700
	with PowerSync PLUS cable	65 700
PC-2 EVO+		
6 outputs. DC Blocker. Distribution bars - OFC 30 QMM. Internal wiring - OFHC 2,5 QMM.		
	with LS-1 EVO+ cable	69 800
	with PowerSync ULTRA cable	59 500
	with LC-2 EVO cable	53 900
	with PowerSync PLUS cable	52 100
POWERCONTROL		
12 outputs. DC Blocker, Distribution bars OFC 30 QMM. Internal wiring OFHC 4,0 QMM. RLC Filtering Block. 16A Relay		
	with LS-1 EVO+ cable	86 200
	with PowerSync ULTRA cable	76 400
	with LC-2 EVO cable	71 200
	with PowerSync PLUS cable	69 500
POWERPRIME		
6 outputs. DC Blocker, Distribution bars OFC 30 QMM. Internal wiring OFHC 4,0 QMM. RLC Filtering Block. 16A Relay		
	with PowerSync ULTRA cable	41 600
	with LC-2 EVO cable	36 600
	with PowerSync PLUS cable	34 900

Power Strips				
PF-2 SE EVO+				
6 outputs. Metal Shielded Chassis. Distribution bars - Silvered OFC 30 QMM. Internal wiring - Silvered OFHC 4 QMM. Advanced RLC filtering block. Iron Powder Filtering Cores. LED indicators of proper work and polarization. Graphite -Gray colour.				
		with LS-1 EVO+ cable	39 600	
		with PowerSync ULTRA cable	29 600	
PF-2 EVO+				
6 outputs. Metal Shielded Chassis. Distribution bars - OFC 30 QMM. Internal wiring - GigaWatt Powerlink OFHC 4 QMM. Advanced RLC filtering block. Iron Powder Filtering Cores. LED indicators of proper work and polarization.				
		with PowerSync ULTRA cable	23 500	
		with LC-2 EVO cable	17 600	
		with PowerSync PLUS cable	15 800	
		with PowerSync cable	14 500	
PF-1 EVO				
6 outputs. Metal Shielded Chassis. Distribution bars - OFC 30 QMM. Internal wiring - OFHC 4 QMM. Iron Powder Filtering Cores. LED.				
		with LC-2 EVO cable	10 900	
		with PowerSync PLUS cable	8 900	
		with PowerSync cable	7 800	
PF-1e				
6 outputs. Metal Shielded Chassis. Internal wiring - OFHC 2,5 QMM. Iron Powder Filtering Cores.				
		with PowerSync PLUS cable	7 100	
		with PowerSync cable	6 000	
		without cable	4 200	
Power Cords				
LS-2 EVO				
	Silver plated OFHC, solid-core, twisted conductors. FEP dielectric, Multi Layer PVC external isolation. Copper shielding.		1,5 m	39 000
	SE version Loss-free Nano-crystal Alloys Passive Filter. G-050 SM/G-070 SM Metal Body, Rhodium Plated Plugs.		next 0,5 m	13 300
LS-1 EVO+				
	Silver plated OFHC, solid-core, twisted conductors. FEP dielectric, Multi Layer PVC external isolation. Copper shielding.		1,5 m	23 500
	Loss-free Nano-crystal Alloys Passive Filter. G-015/G-035 Metal Body, Rhodium Plated Plugs.		next 0,5 m	7 700
PowerSync ULTRA				
	8x 1,6 QMM. OFHC multistrand (7 leads) conductors. PE dielectric. PVC external isolation.		1,5 m	12 600
	Aluminum foil static shield, 100% coverage. G-050SM/G-070SM Metal Body, Rhodium Plated Plugs.		next 0,5 m	2 300
LC-2 EVO				
	7 x 1,5 QMM. OFHC solid-core conductors. PE dielectric. PVC external isolation.		1,5 m	6 200
	Aluminum foil static shield, 100% coverage. G-010/G-030 Rhodium Plated Plugs.		1,0 m	5 700
			next 0,5 m	1 200

PowerSync PLUS			
	3x 2,5 QMM. OFHC multistrand (12 strands per lead). PE dielectric. PVC external isolation. Aluminum foil static shield, 100% coverage. G-010/G-030 Standard Plugs.	1,5 m	4 200
		1 m	3 700
		next 0,5 m	800
PowerSync			
	3x 2.0 QMM. OFHC multistrand (10 strands per lead). PE dielectric. PVC external isolation. Aluminum foil static shield, 100% coverage. G-010/G-030 Standard Plugs.	1,5 m	2 800
		1 m	2 600
		next 0,5 m	600

Accessories			
	G-040 SCHUKO for Assembly		400
	G-044 SCHUKO Wall Socket		1 500
	G-044 Duplex SCHUKO Wall Socket		2 300
	IEC320-C5 / IEC320-C7 Plug Adapter		400
	LC-Y EVO 3X4 In-Wall Cable (1 meter)		400
	PowerSync Power Supply cable (1 meter)		600
	G-16A Installation Circuit Breaker		2 000
	G-16A 2P 2-Pole Installation Circuit Breaker		4 200
	Rolling-Ball Isolation System Anti-Vibration Feet. 4 pcs set in a Wooden Box		7 800
	Full Ceramic Isolation System Anti-Vibration Feet. 4 pcs set in a Wooden Box		14 400

Options			
	Customized LED display color		1 100
	Rolling-Ball Isolation System Anti-Vibration Feet for PC conditioners		6 600